



Ribble Enviro Ltd

www.ribble-enviro.co.uk

RAE MiniRAE 2000

Portable Handheld VOC Monitor

The rugged **MiniRAE 2000** is the smallest pumped handheld volatile organic compound (VOC) monitor on the market. Its Photoionization Detector's (PID) extended range of 0-10,000 ppm makes it an ideal instrument for applications from environmental site surveying to HazMat/Homeland Security.



Key Features

Proven PID technology The patented 3D sensor provides a 3-second response up to 10,000 ppm and sets a new standard for resistance to moisture and dirt.

Self-cleaning lamp and sensor Our patented self-cleaning lamp and sensor minimize the need for maintenance and calibration.

The MiniRAE 2000 lamp and sensor can be taken apart in seconds for easy maintenance without any tools!

Measure more chemicals than with any other PID With over 100 Correction Factors built into the **MiniRAE 2000** memory and the largest printed list of Correction Factors in the world (300+), RAE Systems offers the ability to accurately measure more ionizable chemicals than any other PID. When a gas is selected from the MiniRAE 2000's library, the alarm points are automatically loaded into the meter.

User friendly screens make it easy to use for simple applications and flexible enough for sophisticated operations.

Drop-in battery When work schedules require putting in more than the 10 hours supplied by the standard NiMH battery, the drop-in alkaline pack supplied with every MiniRAE 2000 lets you finish the job.

Rugged Rubber Boot The standard rubber boot helps assure that the MiniRAE 2000 survives the bumps and knocks of tough field use.

Strong, built-in sample pump draws up to 100 feet (30m) horizontally or vertically.

Tough flexible inlet probe

Large keys operable with 3 layers of gloves

Easy-to-read play with backlight.

Stores up to 267 hours of data at one minute intervals for downloading to PC (with the datalogging option).

3-year 10.6 eV lamp warranty

Applications

HazMat/Homeland Security

- Initial PPE (personal protective equipment) assessment
- Leak detection • Perimeter establishment and maintenance • Spill delineation • Decontamination • Remediation

Industrial Hygiene/Safety

- Confined Space Entry (CSE) • Indoor Air Quality (IAQ) • Worker exposure studies

Environmental

- Soil and water headspace analysis • Leaking underground storage tanks • Perimeter fence line monitoring • Fugitive emissions (EPA Method 21) • Vapor recovery breakthrough • Landfill monitoring

Ribble Enviro Ltd
Unit 5 Gisburn Business Park
Gisburn Road
Gisburn
Lancashire BB7 4JP

Tel: 01200 445804
Fax: 01200 445809
Email: sales@ribble-enviro.co.uk
Web: www.ribble-enviro.co.uk



Specification *

Default Sensor Settings **

Gas Monitor	Range (ppm)	Resolution (ppm)	Response Time (T90)
VOCs	0 - 999 ppm	0.1 ppm	< 3 sec

Detector Specification

Size 8.2"L x 3.0"W x 2.0"H (21.8 x 7.62 x 5.0 cm)

Weight 20 oz with battery pack (553g) w/o rubber boot

Sensor Photoionization sensor with standard 10.6 eV or optional 9.8eV or 11.7 eV UV lamp

Battery • Rechargeable, external, field replaceable Nickel-Metal-Hydrate (NiMH) battery pack • Alkaline battery holder (for 4 AA batteries)

Operating Period 10 hours continuous operation

Display Large LCD, backlight activated manually, with alarms or darkness

Keypad 1 operation and 2 programming keys

Direct Readout • VOCs as ppm by volume • High and low values • STEL and TWA (in hygiene mode) • Battery and shut down voltage

Alarms 90 dB buzzer and flashing red LED to indicate exceeded preset limits • High: 3 beeps and flashes per second • Low: 2 beeps and flashes per second • STEL and TWA: 1 beep and flash per second • Alarms automatic reset or latching with manual override • Optional plug-in pen size vibration alarm • User adjustable alarm limits

Calibration Two point field calibration of zero and standard reference gas. Calibration memory of 8 calibration gases, alarm limits, span values and calibration date

Datalogging Optional 267 hours (at one minute intervals) with date/time. Header information includes monitor serial number, user ID, site ID, date and time
flow condition

Low Flow Alarm Auto shut-off pump at lo

Communication Download data and upload instrument set up from PC through RS-232 link to serial port

Temperature 14° to 104°F (-10° to 40°C)

Humidity 0% to 95% relative humidity (non-condensing)

EM/RFI Highly resistant to EMI /RFI. Compliant with EMC Directive 89/336/EEC

IP-rating IP-55: protected against dust, protected against low pressure jets of water from all directions

Hazardous Area • US and Canada: UL and cUL, Classified for use
Approval in Class I, Division 1, Groups A, B, C and D hazardous locations

• Europe: ATEX II IG EEx ia IIC T4

Attachment Durable bright yellow rubber boot w/belt clip & wrist strap

Warranty Lifetime on non-consumable components (per RAE Systems Standard Warranty), 3 years for 10.6.V PID lamp, 1 year for pump and battery

* **On** going projects to enhance our products means that these specifications are subject to change

** Performance based on isobutylene calibration

MiniRAE 2000 and Accessories Monitor only includes:

- 10.6eV, 9.8eV or 11.7eV as specified
- RAE Systems UV lamp: 10.6eV, 9.8eV or 11.7as specified
- 5-inch Flex-I-Probe
- External filter
- Rubber boot with belt clip
- Alkaline battery adapter
- Tool kit
- Lamp cleaning kit
- Nickel-Metal-Hydrate battery
- 120/230 V AC/DC wall adapter (if specified)
- Operation and maintenance manual

Monitor with accessories kit adds:

- Hard transport case with pre-cut foam
- 5 porous metal filters and O-ring
- Organic vapor zeroing adapter
- Gas outlet port and tubing

Optional calibration kit adds:

- 10 ppm isobutylene calibration gas, 34L
- Calibration regulator and flow controller

Datalogging monitor adds:

- ProRAE Suite software package for Windows 98, NT, 2000 and XP
- Computer interface cable

Optional Guaranteed Cost of Ownership Program:

- 4-year repair and replacement guarantee • Annual maintenance service



DISTRIBUTED BY:

Ribble Enviro Ltd

www.ribble-enviro.co.uk

UNIT 5 GISBURN BUSINESS PARK,
GISBURN ROAD, GISBURN
LANCASHIRE BB7 4JP
TEL: 01200 445804 FAX: 01200 445809
EMAIL: sales@ribble-enviro.co.uk

